

SIP Pickup-Schwader AIR 285 / 50 ALPIN

Represented by Rigitrac, www.knuesel-sepp.ch



The innovative AIR pick-up rake is a major advance in raking technology.

The pick-up technology is designed to prevent the loss of sensitive leaves and the introduction of soil, sand and stones into the swath to ensure the harvesting of high-quality forage. Gentle processing means that more nutrients are retained in the forage, which is particularly important for hay and silage.

The pick-up rake is therefore a valuable machine for farmers who value high forage quality and efficient work processes.

Flexible pick-up: The segmented flexible pick-up unit enables excellent ground tracking. The spring tines are bent against the direction of travel, creating a trailing effect that ensures the forage is picked up gently and quickly from the ground and prevents soiling of the forage.

Free-rotating patented discs: The free-rotating discs near the pick-up unit ensure high responsiveness and excellent adaptation to the terrain and reduce wear on the pick-up unit.

Airy windrow: The conveyor belt creates an airy windrow. The windrow is turned when it is deposited, thus eliminating the need for a rotary operation. The swath can be deposited on the left or right.

Uniform swath formation: The pick-up rake forms uniform swaths, making subsequent work steps such as picking up or baling more efficient.

Gentle handling of the forage: By using a conveyor belt, the forage is subjected to less mechanical stress and remains largely undamaged, which increases the quality of the forage.

Efficient operation: Thanks to the gentle treatment and uniform swath formation, working time is optimized and efficiency in the field is increased.

Reduction of dirt and impurities: As the forage is treated gently, the intake of dirt and stones is also reduced, which further improves the quality of the forage.

Brand	SIP AIR 285 / 50 ALPIN
Working width	2850mm
Conveyor belt width	500mm
Oil quantity	Hydraulic self-supply
PTO speed	540/1000 L/R
Power requirement	52 hp
Cultivation	Three-point cat. I / II
Weight	630 kg
Special features	Flexible pick-up Swath delivery left / right possible Spring tine loss protection Free-rotating patented plates

