

Rigitrac SKH 75

www.rigitrac.ch/produkte-1/rigitrac-skh-75/



Tractor described by the producer:

The innovative Swiss tractor Rigitrac SKH 75 with a central pivot joint in the vehicle frame. The central pivot joint ensures implement guidance via the respective axle and ensures optimum ground tracking. The excellent torque characteristics of the engines and the extremely smooth running make for comfortable work. The four equally sized wheels and the various steering options make it very gentle on the ground. The combination of four-wheel steering and central swivel joint also enables a low center of gravity with very high off-road mobility and a low tare weight. The hydrostatic driving and maneuverability of the Rigitrac impresses every driver when using the front implement and front loader. The excellent view of the attachments and the entire working area enables precise and productive work. The Rigitrac is a mountain tractor, tractor and farm loader in one and is therefore very versatile. Its technical qualities are unique.

- Various steering options (front steering, four-wheel steering, crab steering, delayed steering)
- Extreme maneuverability thanks to maximum wheel angle and narrow chassis design
- Operator-friendly, excellent visibility of the attachments
- Revolutionary chassis frame with central pivot joint
- Extremely suitable for slopes thanks to low center of gravity
- Axle-mounted front and rear attachments
- Four wheels of the same size, without wheel run-out, gentle on the ground
- Enormous stability when using the front loader, thanks to the center pivot joint
- High axle loads for use with implements
- Swiss tractor manufacturer – made in Switzerland

Model Rigitrac SKH 75

Motor / rated power PS

Deutz Motor, TCD 3.6 / 116 hp / Turbo / 4
Cylinder

Travel drive

Stepless / 2 groups

Hydraulics / control valves

3 DW rear / 1 free return 1 DW front / 1 free
return (expandable to 3 DW) Volume flow 60lt
/2000 rpm

PTO shafts / PTO shaft speed

Front 1000 rpm / rear 540 rpm, powershiftable

Weight

Unladen weight: 3700 kg Payload: 2800 kg Axle
loads: 4500 kg / per axle

Special features

Four-wheel steering / crab steering / delayed
steering Central center pivot joint Low center of
gravity Low tractor height 2.48m