



CC 36

Motor mower / single axle machine



Technical data

| | CC 36 |
|--|--------------------------------------|
| Drive system - Engine | |
| Engine type | B&S-Vanguard |
| Number of cylinders | 1 |
| Fuel | Gasoline |
| Fuel tank | 3.6 l |
| Performance | 7.4 kW (10 HP) |
| Stepless adjustable hydrostatic traction drive | yes |
| Electromagnetic clutch for implement drive | yes |
| Brake | Hydrostatic |
| PTO shaft speed | 854 1/min |
| Drive system - Engine 2 | |
| Engine type | B&S-Vanguard |
| Number of cylinders | 1 |
| Fuel | Gasoline |
| Performance | 10.4 kW (14 HP) |
| PTO shaft speed | 854 1/min |
| Attachment mounting | |
| Aebi quick-fit attachment connector system | yes |
| Min. cutter width | 1,450 mm |
| Max. cutter width | 2,200 mm |
| Tyres | |
| Basic tyres | 5.0-10 AS Spiked rollers four-row |
| Double wheels/cage wheels/double cage wheels/spiked wheels | yes |
| Speed | |
| Forward speed | 0-3 km/h / 0-6 km/h / 0-8 km/h |
| Reverse speed | 0-5 km/h |



CC 36

Equipment

| | |
|---------------------|--------|
| LED lighting system | option |
| Wheel disconnection | option |
| Parking brake | option |

Weights

| | |
|---|--------|
| Weight (incl. base tyres; without attachment) | 156 kg |
|---|--------|

Gallery



 **aebi schmidt**
group

© Aebi Schmidt Group
www.aebi-schmidt.com

Aebi Schmidt Holding AG
CH-8050 Zurich, Switzerland

All rights reserved. Technical data is
subject to change.
Illustrations are not binding. Errors and
amendments excepted.

Document created on 9 JUN 2024

